

ALL PURPOSE EPOXY

All Purpose Structural Adhesive

Product Description

Pioneer All Purpose Epoxy is a 100% solids thermosetting plastic compound that forms strong bonds on a wide variety of rigid materials— glass, metals, ceramics, concrete, wood and some plastics (except polyethylene, soft PVC and Teflon).



Key Features

- Multi-purpose
- Heavy-duty epoxy adhesive
- 100% solids content
- Solvent-free formulation
- Low VOC
- Non-flammable
- Non-shrinkable
- Water-resistant
- Solvent-resistant
- Chemical-resistant
- Sandable and Paintable

Applications

- Bonding, patching, filling and sealing of new or worn-out boat, furniture, porcelain, metal or concrete
- Bonding decorative and metal hardware to wood, metal and concrete
- Installing ceramics or glass tiles to wooden or concrete surfaces
- Adhesive for metal nameplates in automotive and appliances industry
- Repairing or joining marble blocks to marble, wood or concrete

Application Procedure

Product Specifications / Typical Properties / Physical Characteristics

Table 1. Wet Properties*

Parameters	Component A (RESIN)	Component B (HARDENER)
1. Appearance	Pink, soft paste	Beige, soft paste
2. Specific Gravity	1.81	1.47
3. Viscosity @ 25°C	1,500,000 cps	745,000 cps
4. Solids Content	100%	100%

Table 2. Mixed State Properties*

Parameters	Results
1. Mixing Ratio	1 part A: 1 part B (by volume)
2. Appearance	Pink
3. Potlife @ 24-33°C	60-120 minutes
4. Setting Time @ 24-33°C	6-8 hours

Table 3. Cured State Properties*

Parameters	Results
1. Full cure time	72 hours
2. Hardness (after 24 hours), shore D	80 minimum
3. Shrinkage	nil
4. Water resistance	Excellent
5. Chemical Resistance	Resistant to most acids, alkalis and other organic solvents
6. Weathering Resistance	Color will fade through time (epoxy-based products are typically not UV-resistant)
7. Lap Shear Strength (wood-wood) ASTM D905	>500 psi
8. Tensile Strength ASTM D638	2707 psi
9. Flexural Strength ASTM D790	5034 psi
10. Compressive Strength ASTM D695	6216 psi

*Typical Values and characteristics only.

A. Surface Preparation

Surface contaminants such as dirt, grease, oil or wax must be removed from areas to be joined. Clean surfaces by sanding, sandblasting or brushing for stronger bonds. Surfaces should be clean and ready for application before the adhesive is mixed.

B. Mixing

Mix equal parts by volume of components A and B. Better to use separate spatulas (or spoon) to avoid contamination. Blend thoroughly until color streaks disappear and a uniform color is obtained. To avoid waste, prepare a quantity just enough to be consumed within 1 hr.

C. Method

1. Apply mixed compound with a putty knife or spatula on one or both faces of glue joints.
2. Join surfaces with sufficient pressure to ensure complete contact.
3. Allow to cure or to harden.
4. Unnecessary handling should be avoided until cure is complete. On its uncured state, scrape off excesses from edges or joints or immediately spread out the mixture on surfaces to be settled, filled or patched.

D. Cleaning

Clean all tools or equipment used while adhesive is still in its uncured state. Use Pioneer Epoxy Reducer or solvents to clean tools and spills.

Packaging

SKU	Packaging	Weight of set, kg	Quantity per box
Gallon set	Tin can	11.28	2 sets
Quart set	Tin can	2.80	6 sets
Pint set	Tin can	1.43	12 sets
1/2 Pint set	Tin can	0.71	24 sets
1/4 Pint set	Tin can	0.29	50 sets
35g tube set	Tube	0.035	24 sets

Note: 1 set = 1 pc component A + 1 pc component B

Certification and Compliance

Type	Component A	Component B	Limits
1. Volatile Organic Content (VOC), g/L	1.7	0.4	VOC limits • Multipurpose construction adhesives- 70 g/L • Wood Flooring adhesive- 100 g/L
2. Lead (Pb) content, ppm	<10	<10	Maximum concentration value (MCV) allowed is <1000 ppm

Storage

Store in a dry place at ambient temperature. Keep containers tightly closed when not in use.

Shelf Life

24 months from manufacturing date when kept in a sealed, unopened container following the required storage condition.

Health and Safety Precautions



WARNING

Hazards

Causes skin and eye irritation.
May cause an allergic skin reaction.

Precaution

Wash skin thoroughly after handling.
Wear protective gloves/clothing/eye/face protection.
Contaminated work clothing should not be allowed out of the workplace.

If on skin or hair: Wash with plenty of soap and water. Take off contaminated clothing and wash before re-use. If skin irritation or rash occurs, get medical attention

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists, get medical advice/attention.

Collect spillage.

KEEP OUT OF REACH OF CHILDREN.

Warranty and Disclaimers

Unless an additional warranty is specifically stated on the applicable product packaging or product literature, Pioneer warrants that each Pioneer product conforms with the applicable Pioneer product specification at the time of shipment, and when properly used and maintained in accordance with Pioneer's current published Technical Data Sheet (TDS), will serve the purpose for which it is intended. The recommendations and statements in Pioneer's TDS are based on good building practice but are not, by any means, an exhaustive statement of all relevant information. Pioneer shall not be liable for the recommendations in its TDS and the performance of the relevant Product. Pioneer shall also not be liable for any claims, damages or defects arising from, or in any way attributable to poor workmanship, incorrect design or detailing, use of the Pioneer product in unsuitable conditions, and force majeure.

Pioneer MAKES NO OTHER WARRANTIES, CONDITIONS OR REPRESENTATIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF DEALING, CUSTOMER OR USAGE OF TRADE. If the Pioneer product does not conform to this warranty, then the sole and exclusive remedy is, at Pioneer's option, the replacement of the Pioneer product or refund of the purchase price.

Limited Liability

Except where prohibited by law, Pioneer will not be liable for any loss or damage arising from the use or application of the Pioneer product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.

TDS Pioneer - 022019 Version

Pioneer Adhesives, Inc.
Formerly Republic Chemical Industries, Inc.

ISO 9001:2015 and ISO 14001:2015 Certified

LMS Complex, Carmelray Industrial Park 1, Calamba City, Laguna, 4028 Philippines
Product Information: www.pioneer-adhesives.com • Email: info@pioneerph.com • Tel: + 632 918-1000

Pioneer
Do it right.