

Painter's Buddy Acrylic Gap Sealant

Product Description

Pioneer Pro Painter's Buddy Acrylic Gap Sealant is a multipurpose, interior/ exterior sealant that when cured, forms a flexible, durable, weather resistant seal that bonds to most common building materials. It is fully paintable and sandable when cured. Uncured sealant cleans up easily with water.



Key Features

- Paintable
- Sandable
- Mildew Resistant
- Non-Yellowing
- Permanently Flexible
- Weatherproof / Waterproofs
- Interior/Exterior use
- Does not bleed, stain, discolour

Product Specifications / Typical Properties / Physical Characteristics

Table 1.

Physical Properties, Uncured state*

Parameters	Results
Appearance	White Thixotropic Paste
pH	7.0-8.7
Slump	Nil
Specific Gravity	1.59-1.65
Tack Free Time	19 minutes to 1 hour and 40 minutes depending on temperature and relative Humidity
Tooling time	10-15 mins

*Typical data only and should not be used in writing specifications.

Table 2. Physical Properties, Cured State

Parameters	Results
Hardness, Shore A	30
Staining	None
Elongation	200-300%
Adhesion	
- Wood	- Good
- Concrete	- Good
- Cement	- Good
- Plastic	- Good
Volatile Organic Component	<9.8 g/L

Applications

- Interior/Exterior Applications
- Windows
- Metal Channels
- Store Fronts
- Sealing of Marine Cabins and Windows

Application Procedure

All surfaces should be clean and free of dirt, dust, debris, any oils and grease prior to application.

1. Cut nozzle of cartridge/pouch to desired bead size
2. Insert in standard cartridge gun if applicable
3. Apply Pioneer Pro Painter's Buddy Acrylic Gap sealant into the joint
4. Tool off excess sealant

Application Equipment

- Caulking gun

Packaging

- 300 mL cartridge
- 100 g pouch

Storage

When stored in the original unopened container at or below 32°C, containers should always be kept sealed when not in use.

Shelf Life

18 months

Health and Safety Precautions

Product may cause eye and skin irritation on prolonged exposure. In case of eye contact, flush thoroughly with running water. Wash thoroughly after handling.

KEEP OUT OF REACH OF CHILDREN**Warranty and Disclaimers**

Unless an additional warranty is specifically stated on the applicable product packaging or product literature, Pioneer warrants that each Pioneer product conforms with the applicable Pioneer product specification at the time of shipment, and when properly used and maintained in accordance with Pioneer's current published Technical Data Sheet (TDS), will serve the purpose for which it is intended. The recommendations and statements in Pioneer's TDS are based on good building practice but are not, by any means, an exhaustive statement of all relevant information. Pioneer shall not be liable for the recommendations in its TDS and the performance of the relevant Product. Pioneer shall also not be liable for any claims, damages or defects arising from, or in any way attributable to poor workmanship, incorrect design or detailing, use of the Pioneer product in unsuitable conditions, and force majeure.

Pioneer MAKES NO OTHER WARRANTIES, CONDITIONS OR REPRESENTATIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF DEALING, CUSTOMER OR USAGE OF TRADE. If the Pioneer product does not conform to this warranty, then the sole and exclusive remedy is, at Pioneer's option, the replacement of the Pioneer product or refund of the purchase price.

Limited Liability

Except where prohibited by law, Pioneer will not be liable for any loss or damage arising from the use or application of the Pioneer product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.