

Mighty Gasket Liquid Grey Engine Sealant

Product Description

Pioneer Mighty Gasket Liquid Grey Engine Sealant is a high viscoelastic type sealant capable of joining uneven surfaces. It enhances seal and helps prevent leakages in motorcycle engine parts

Key Features

- Easy to apply due to low viscosity at room temperature
- Non-hardening for easy dismantling of parts
- Fast setting time
- It is resistant to heat, oil, gasoline and LPG, water, steam, and anti-freeze



Product Specifications / Typical Properties / Physical Characteristics

Table 1: Physical Properties (Uncured)

Parameters	Results
Appearance	Grey high viscosity liquid
Viscosity @ 30°C	14,000 – 16,000 cps
Solid content	47 ± 3 %
Main Solvent	Hydrocarbon Solvent
Main ingredient	Chloroprene rubber
Setting Time	5 minutes
Dilution	Toluene
Temperature	40°C - 150°C

**Typical data only. Information on this data should not be used for writing specifications.*

Applications

- For joints and gaskets
- Flange surfaces
- Oil filter and drain plug fitting surfaces
- Transmission joined flange surfaces
- Fuel pump joined flange surfaces
- Crank case and cylinder heads
- Carburetor manifolds

Application Procedure

1. Wipe off moisture, oil and all other foreign matters on bonding surfaces.
2. Apply a thin and uniform layer of Mighty Gasket Liquid Grey Engine Sealant on both mating surfaces.

3. Allow to dry before assemble and bolt together.

Packaging

10 g tube
30 g tube

Storage

Store in dry and cool air tight containers

Shelf Life:

12 months

Health and Safety Precautions

Flush immediately with water for any spillage on skin. If spill on eye, flush immediately with water and seek oculist treatment immediately. Highly flammable product.

Do not take internally.

KEEP OUT OF REACH OF CHILDREN.

Warranty and Disclaimers

Unless an additional warranty is specifically stated on the applicable product packaging or product literature, Pioneer warrants that each Pioneer product conforms with the applicable Pioneer product specification at the time of shipment, and when properly used and maintained in accordance with Pioneer's current published Technical Data Sheet (TDS), will serve the purpose for which

it is intended. The recommendations and statements in Pioneer's TDS are based on good building practice but are not, by any means, an exhaustive statement of all relevant information. Pioneer shall not be liable for the recommendations in its TDS and the performance of the relevant Product. Pioneer shall also not be liable for any claims, damages or defects arising from, or in any way attributable to poor workmanship, incorrect design or detailing, use of the Pioneer product in unsuitable conditions, and force majeure.

Pioneer MAKES NO OTHER WARRANTIES, CONDITIONS OR REPRESENTATIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF DEALING, CUSTOMER OR USAGE OF TRADE. If the Pioneer product does not conform to this warranty, then the sole and exclusive remedy is, at Pioneer's option, the replacement of the Pioneer product or refund of the purchase price.

Limited Liability

Except where prohibited by law, Pioneer will not be liable for any loss or damage arising from the use or application of the Pioneer product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.